

SVEZA DECK 350

SVEZA Deck 350* is a special film-faced plywood with an easy-to-use grid pattern, designed for slab formwork. SVEZA Deck 350 comes with 25, 50 and 100 mm grid patterns. These types of lines simplify plywood marking and cutting, as well as rebar placement. This allows the reduction of labor costs at the construction site. The sides of SVEZA Deck 350 are coated with special acrylate-based paint with a high level of water resistance.



Key benefits

- 01 **100% birch plywood**
- 02 **Easy to cut and mark**
- 03 **Easy to put bars**
- 04 **Reduces work time and labor costs**
- 05 **Wear resistant surface**
- 06 **Moisture protection on the edges**
- 07 **Convenient packaging**

Technical specifications

Standard sizes, length x width, mm (ft)	1525x1525 (5x5) 2440/2500x1500/1525 (8x5)
Thickness, mm	8, 21
Surface type	Smooth (F/F)
Film density, g/m ²	120
Wear resistance of the film, cycles in Taber abrasion test	350
Formaldehyde emission class	E1
Density, kg/m ³	640-700
Moisture content, %	5-14
Edge sealing	Water-based acrylic paint
Produced under STO.**	

Strength specifications

DIMENSION		VALUE
Ultimate static bending strength, min MPa	along the outer layer grain	60
	across the outer layer grain	30
Static bending elasticity modulus, min MPa	along the grain	6000
	across the grain	3000

* Production process of plywood with layout grid is patented (registered in the Russian Federation National Register of Utility Models 20.01.15, patent #150519).

** For STO visit "Certificates" section of website.